(Page 1 of 3)

Pie

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-418 Relating to Certification of New Motor Vehicles

CHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Chrysler Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: XCRXT0150120 Displacement: 2.5 Liters (150 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Three Way Catalytic Converter Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection Warm Up Oxidation Catalytic Converter

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gas (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) TLEV certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle <u>Weight (lbs.)</u>	Miles	NMOG	<u></u>	<u>NOx</u>	нсно_	CO (20°F)
0-3750	50,000	0.125	3.4	0.4	0.015	10.0
	100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for NMOG reflect application of a 0.98 RAF for 1999 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	NMOG_	<u></u>	<u>NOx</u>	нсно	<u>CO (20°F)</u>
0-3750	50,000	0.060	1.8	0.1	0.001	4.1
	100,000	0.068	2.1	0.1	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this $\frac{9^{+1}}{2}$ day of July 1998.

R. B. Summerfield, Chief

Mobile Source Operations Division

E.O.	#	A	9-41	8	
		Page	1	_of_	1


1999 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: _C	hrysler Corpora	<u>tion </u>	Eng Fam:	CRXT01	<u>50120</u> Eva	o Fam: XCRXI	0101G2S
All Eng Codes in	Eng Fam: CA_X	49S	_ 50S	AB96	50	RVR: YES	иох
exh Std: CA Tier	-1TLEV	X LEV	ULEV	SU	LEV;	US EPA Tier	1
Jeh Class(es):	PCLDT1_X	LDT2_X	MDV1	MDV2_	MDV3	MDV4	_ MDV5
Single Cert Std	for Multi-Class	Eng Fam: LD	<u>T1</u> (Spec:	ify: N/	A, LDT1, MD	V1, MDV2, MI	DV3, MDV4)
Fuel Type(s): De	edicated X Fle	x-FuelD	ual-Fuel_	Bi-	Level G	asoline <u>X</u>	Diesel
	CNGLNG	LPG M	85	Other (specify)		
ovh Emic Test F	Fuel(s): Indo	_ CBG <u>X</u> CN	GLP	G M	85Othe	r(specify) .	
EXII. EMED TOO	Diesel: 13	CCR 2282	or 40 CF	R 86.11	3-90or	40 CFR 86.	113-94
Dunnamatira Emis	ssion Test Proce	dure: Calif	ornia		Federal	Х	
Evaporative Emis	Std AMA	Mod AMA	Mfr A	DPX_	Other (Specify)	
Service Accum:	dure: N/A S	tđ Equi	 .v_X_ R/:	L Test	Proce: SHED	Pt S	ource <u>X</u>
NMOG Test Proced	ation: I-4 Disp	lacement:	/ 2	,5Li	ters	/ 150 C	ubic Inches
Engine Configura	nder: 2	Pat	ed HP:	120/120)/125 @	5200/5400	/5400RPM
			Drive.	FWD	RWD_X	4WD-FT	4WD-PT_X
Engine: Front1	X Mid Re						
Exhaust ECS (eg	., EGR, MFI, TC,	(us	e abbrevi	ations	per SAE J19	30 JUN93)	
		Trans. Type	ETW	DPA	Ignition	EGR	Catalyst
Engine Code (also list	Vehicle Models (if coded see	M5	or	or	(ECM/PCM)	System	Converter
CA/49ST/50ST)	attachment)	A4	Test Wt.	RLHP	Part No.	Part No.	Part No.
CA-100	XJTL72	АЗ	3375	s	56041485AC	None	52019480AF
(CA)	XJTL74			E			52019435AB
CA-300	TJJL77		3625	-	56041462AC	·	52101129AA
(CA)	10027			A			52019435AB
	XJIL72	M5	3375	T	56041481AC		52019480AF
(CA)	XJTL74			A			52019435AB
			3500	C H	[5		
	XJJL72	٠.		E			
	XJJL74		3625	D			
CM-300	TJJL77		3625		56041458AC		52101129AA
(CA)							52019435AB
CM-500	AN1L61		3750		56040027AA		52103269AA
(CA)	ANIL62				56040027AB		52021007A9
	ANILII		3875				
	·	1					
	Light and the second	_ 	<u> </u>				:

Date Issued: 04/30/98

Revisions:

Vehicle HFR: CHRYSLER	Engine Family: XCRXT0150120 Evaporative Fam: XCRXE0101G2S	Certificate #:
		California
Hodel 10	Car Line	Sales
X 31 L 7 2	Cherokee 2WD	YES
XJTL74	Cherokee 2WD	YES
XJJL72	Cherokee 4WD	YES
X J.J.L.74	Cherokee 4WD	YES
AN1L31	Dakota Pickup 2WD	YES
AN1L61	Dakota Pickup 2WD	YES
AN1162 .	Dakota Pickup 2WD	YES
Lift L	Wrangler 4WD	YES
Rated HP		•
XU - 125 @ 54	009	
AN - 120 0 5200 TJ - 120 0 5400	200	



ATTACHMENT TO SDS PAGE 1 0F EXECUTIVE ORDER A-9-418

1999 XCRXT0150120

Chrysler Corporation Family Tire Usage

LOADED VEHICLE WEIGHT

MODEL ENG TRANS C GVW TYPE ETW USE YR COD MFG OPT TIME HP F R (LINE 1 IS 20 DEG COEFFS, LINE 2 IS 50 ANIL31 EPE DDK RA Y 4780 C 3875 STD 99 TMD TZA 14.61 12.7 35 35 39.53 0.03456 ANIL31 EPE DDK RA Y 4780 C 3875 STD 99 TME TZA 14.61 12.7 35 35 39.53 0.03456 OPT 99 TME TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 ANIL61 EPE DDK RA Y 4580 C 1750 STD 99 TMD TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 0PT 99 TST TZA 13.51 12.9 15 35 35.82 0.03856	в С
A MKT LVW TIRE DESCRIPTION DOWN *DYNO PRES TARGET A B C SET A USE YR COD MFG OPT TIME HP F R (LINE 1 IS 20 DEG COEFFS, LINE 2 IS 50 USE YR COD MFG OPT TIME HP F R (LINE 1 IS 20 DEG COEFFS, LINE 2 IS 50 O.03456 ANIL31 EPE DDK RA Y 4780 C 3875 STD 99 TMD TZA 14.61 12.7 35 35 39.53 0.03456 OPT 99 TME TZA 14.61 12.7 35 35 39.53 0.03456 OPT 99 TS1 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TXS TZA 13.74 13.2 35 35 38.15 0.03856 ANIL61 EPE DDK RA Y 4580 C 3750 STD 99 TMD TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436	в С
MODEL ENG TRANS C GVW TYPE ETW USE YR COD MFG OPT TIME HP F R (LINE 1 IS 20 DEG COEFFS, LINE 2 IS 50 DEG COEFFS, LINE 2 I	DEG WHEN NEEDE
MODEL ENG TRANS C GWW TYPE ETW USE IX COS MIC OF THE TZA 14.61 12.7 35 35 39.53 0.03456 ANIL31 EPE DDK RA Y 4780 C 3875 STD 99 TMD TZA 14.61 12.7 35 35 39.53 0.03456 OPT 99 TME TZA 14.61 12.7 35 35 39.53 0.03456 OPT 99 TS1 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 ANIL61 EPE DDK RA Y 4580 C 3750 STD 99 TMD TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436	
ANIL31 EPE DDK RA Y 4780 C 3875 STD 99 TMD TZA 14.61 12.7 35 35 39.53 0.03456 OPT 99 TME TZA 14.61 12.7 35 35 39.53 0.03456 OPT 99 TS1 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 12.74 13.0 35 35 38.15 0.03856 ANIL61 EPE DDK RA Y 4580 C 3750 STD 99 TMD TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436	
ANILS1 EPE DDK RAY 4780 C 3875 STD 99 TMD TZA 14.61 12.7 35 35 39.53 0.03456 OPT 99 TME TZA 14.61 12.7 35 35 39.53 0.03456 35.94 0.03142 OPT 99 TS1 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TXS TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436	
OPT 99 TME TZA 14.61 12.7 35 35 39.53 0.03456 35.94 0.03142 OPT 99 TS1 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TXS TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 35 37.14 0.03436	
35.94 0.03426 OPT 99 TS1 TZA 13.74 13.2 35 35 38.15 0.03656 34.68 0.03505 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 34.68 0.03505 OPT 99 TXS TZA 12.74 13.0 35 35 34.68 0.03505 OPT 99 TXS TZA 12.74 13.0 35 35 34.70 0.04084 39.73 0.03713 ANIL61 EPE DDK RA Y 4580 C 1750 STD 99 TMD TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 13.51 12.9 35 35 35.82	
OPT 99 TS1 TZA 13.74 13.2 35 35 38.15 0.03656 34.68 0.03505 OPT 99 TS2 TZA 13.74 13.2 35 35 38.15 0.03856 34.68 0.03505 34.68 0.03505 34.68 0.03505 34.68 0.03505 34.68 0.03505 34.68 0.03713 37.14 0.03436 33.76 0.03124 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 33.76 0.03124 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 33.76 0.03124	
ANIL61 EPE DDK RA Y 4580 C 3750 STD 99 TMD TZA 14.40 12.4 35.35 37.14 0.03436 0.03436 0.03124 0.07 99 TME TZA 14.40 12.4 35.35 37.14 0.03436 0.03124 0.07 99 TME TZA 14.40 12.4 35.35 37.14 0.03436 0.03124 0.07 99 TME TZA 14.40 12.4 35.35 37.14 0.03436 0.03124 0.07 99 TME TZA 14.40 12.4 35.35 35.82 0.03856	
ANIL61 EPE DDK RA Y 4580 C 3750 STD 99 TMD TZA 13.74 13.2 35 35 38.15 0.03856 OPT 99 TXS TZA 12.74 13.0 35 35 43.70 0.04084 39.73 0.03713 OPT 99 TMD TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 13.51 12.9 35 35 35.82 0.03856	
ANIL61 EPE DDK RA Y 4580 C 3750 STD 99 TMD TZA 14.40 12.4 35.35 37.14 0.03436 0.03124 OPT 99 TME TZA 14.40 12.4 35.35 37.14 0.03436 33.76 0.03124 OPT 99 TME TZA 14.50 12.4 35.35 37.14 0.03436 0.03124 0.03436 0.03436 0.03124 0.03436 0.03124 0.03436 0.03124 0.03436 0.03436 0.03124 0.03436 0.03124 0.03436 0.0343	
OPT 99 TXS TZA 12.74 13.0 35 35 43.70 0.04084 39.73 0.03713 ANNIL61 EPE DDK RA Y 4580 C 3750 STD 99 TMD TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 OPT 99 TME TZA 13.51 12.9 35 35 35.82 0.03856	
ANIL61 EPE DDK RA Y 4580 C 3750 STD 99 TMD TZA 14.40 12.4 35.35 37.14 0.03436 OPT 99 TME TZA 14.40 12.4 35.35 37.14 0.03436 OPT 99 TME TZA 13.51 12.9 35.35 37.14 0.03436 OPT 99 TS1 TZA 13.51 12.9 35.35 35.82 0.03856	
ANIL61 EPE DDK RA Y 4580 C 3750 STD 99 TMD TZA 14.40 12.4 35.35 37.14 0.03436 33.76 0.03124 0.03436 0.03436 0.03124 0.03436 0.03124 0.03436 0.03124 0.03436 0.03124 0.03436 0.03124 0.03436 0.03436 0.03124 0.03436 0.	
ANIL61 EPE DDK RA 1 4380 C 3134 0.03124 OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03124 OPT 99 TS1 TZA 13.51 12.9 35 35 35.82 0.03856	
OPT 99 TME TZA 14.40 12.4 35 35 37.14 0.03436 33.76 0.03124 OPT 99 TS1 TZA 13.51 12.9 35 35 35.82 0.03856	
33.76 0.03124 OPT 99 TS1 TZA 13.51 12.9 35 35 35.82 0.03556	
OPT 99 TS1 TZA 13.51 12.9 35 35.82 0.03856	
OPT 99 TS1 TZA 13.31 12.3 35 50 0.03505	
32.57	
OPT 99 TS2 TZA 13.51 12.9 35 35 35.82 0.03856	
OPT 99 TS2 TZA 13.51 12.9 35 35 35.62 32.57 0.03505	
75 75 47 10 0.04084	
OPT 99 TXS TZA 12.7 35 35 41.10 37.36 0.03713	
0.03436	
ANIL62 EPE DDK RA Y 4660 C 3750 STD 99 TMD TZA 14.40 12.4 35 35 37.14 33.76 0.03124	
0.03436	
OPT 99 TME TZA 14.40 12.4 35 35 37.14 33.76 0.03124	
OPT 99 TS1 TZA 13.51 12.9 35 35.82 0.03856	
32.57 0.03505	
OPT 99 TS2 TZA 13.51 12.9 35 35.82 0.03856	
32.57 0.03503	
OPT 99 TXS TZA 12.54 12.7 35 35 41.10 0.04084	
37,36	
0.04401 0.04401 0.0625 STD 99 TPN TZA 10.86 15.6 33 33 50.78	
TJJL77 EPE DDQ 4W 1 4430 C 3023 C 3025 C 302	
OPT 99 TMW TZA 10.82 15.9 33 33 46.46 0.04595	•
OPT 99 TMW TZA 10.82 15.9 13 33 40.40 42.23 0.04177	
OPT 99 TMW TZA VKO 11.26 15.2 33 33 42.15 0.04495	
38.32	
OPT 99 TPN TZA VKO 11.10 15.1 33 33 47.45 0.04370	
43.14	
OPT 99 TRN TZA 10.69 15.9 33 33 49.82 0.04551	
45.29 0.04137	
OPT 99 TRN TZA VKO 11.04 15.3 33 33 43.58 0.04563	
39.62	
0.04401 0.43 15.7 33 33 57.97 0.04401	
TJJL77 EPE DGD 4W Y 4450 C 3625 STD 99 TPN TZA 10.43 15.7 33 33 57.97 52.70 0.04001	

REPORT DATE: 04/30/98

99car416

ATTACHMENT TO SDS PAGE 1 OF EXECUTIVE ORDER A-9-418

1999 XCRXT0150120 Chrysler Corporation Family Tire Usage

LOADED VEHICLE WEIGHT

																					•				
													COAST		τ	IRE		cor	.D CO	ELECTRI					
			1	A.		MKT	LVW	TIRE	DE:	SCR.	PTIC	ЭN	DOWN	*DYNO	P	RES	TARGET		8	С		T A	В		С
MODEL	ENG	TRAN	s		VW	TYPE	ETW	USE	YR (מסכ	MFG	OPT	TIME	ĦР	F	R	(LINE 1) DEG	WHEN	NEEDEL
						-				- - -															
								OPT	99 1	MM	TZA		10.40	15.9	3	3 33				0.0459					
																	48.74			0.0417					
		-						OPT	99 ′	IMM	TZA	VKO	10.81	15.2	3	3 33				0.0449					
																	44.82			0.0408					
								OPT	99 '	r PN	TZA	AKO	10.66	15.2	3	3 33				0.0437					
													•				49.62			0.0397					
								OPT	99 '	TRN	TZA		10.27	16.0	3	3 33				0.0455					
																	51.82			0.0413					
								OPT	99 '	TRN	TZA	VKO	10.60	15.4	3	3 33				0.0456					
																	46.08			0.0414					
XJJL7	2 EPE	DDQ	49	Y 4	850	C	3500	STD	99	TM6	TZA		11.68	13.8	3	3 33	49.25			0.0378					
																	44.77			0.0343					
								OPT	99	TRL	TZA		11.35	14.1	_ 3	3 33				0.0393					
				n											_		45.25			0.0357					
XJJL7	4 EPE	DDQ	4W '	Y 4	900	C	3625	STD	99	IM6	TZA		12.03	13.8	. 3	3 33	50.05 45.50			0.0343					
																				0.039					
								OPT	99	TRL	TZA		11.69	14.1	-	دد و	45.98			0.035					
																				0.0350					
XJTL7	2 EPE	DDQ	RW	Y 4	550	С	3375	STD	99	TM6	TZA		12.71	11.9	-	נג נ	39.14 35.58	4		0.0318					
																				0.0352					
								OPT	99	TRL	TZA	•	12.46	12.4			37.78			0.0320					
														13.0						0.0350					
XJTL7	2 EPE	DGD	RW	Y 4	550	С	3375	STD	99	TM6	TZA	•	12.19	12.0	'		40.93			0.031					
											:			12.6						0.035					
								OPT	99	TRL	TZA	•	11.96	12.0	, .		43.16			0.032					
														11.9		כנ כו				0.035					
XJTL7	4 EPE	DDQ :	RW	Y 4	600	С	3375	STD	99	TWO	TAA	•	12.71	41.3		,, ,,	35.58			0.031					
											~~ 1		17 46	12.4		17 23				0.035					
								OPT	39	1KL	1.4A	•	12.46	44.4	٠. ١		37.78			0.032					
						_					mry a		12 10	12.0	, ,	17 77	- · · · · · · · · · · · · · · · · · · ·			0.035					
XJTL7	4 EPE	2 DGD	RW	Y 4	600	С	3375	STD	33	TWO	1 Z.H	•	12.13	12.0	•		40.93			0.031					
								~~~	- 00	י פית	TZA		11 94	12.6		11 77				0.035					
								UPT	77	147	1.44		11.90	15.0	•		43.16			0.032					

**REPORT DATE: 04/30/98**